

ABN: 52 189 407 505 Phone: 1300 577 719 Fax: 1300 366 353 Email: glabe@sealing services.com.au Web: www.global-services.com.au 17 Ryelane Street Maddington WA AUSTRALIA

SAFETY DATA SHEET

# **GLOBAL FLEXITHANE 303 PART A**

Infosafe No.: LQ2H2 ISSUED Date : 15/12/2022 ISSUED by: GLOBAL SEALING SERVICES PTY LTD

### Section 1 - Identification

**Product Identifier** GLOBAL FLEXITHANE 303 PART A

Company Name GLOBAL SEALING SERVICES PTY LTD (ABN 52 189 407 505)

Address

17 Ryelane Street Maddington WA AUSTRALIA

**Telephone/Fax Number** Tel: 1300 577 719 Fax: 1300 366 353

E-mail Address glabe@sealing services.com.au

**Recommended use of the chemical and restrictions on use** Part A liquid component of polyurethane foam system.

## Section 2 - Hazard(s) Identification

### GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia. Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition) Acute toxicity: Category 4 - Inhalation Skin corrosion/irritation: Category 2 Eye damage/irritation: Category 2A Sensitisation - respiratory: Category 1 Sensitisation - skin: Category 1 Carcinogenicity: Category 2 Specific target organ toxicity (single exposure): Category 3 (Respiratory tract irritation) Specific target organ toxicity (repeated exposure): Category 2

Signal Word (s) DANGER

### Hazard Statement (s)

H315 Causes skin irritation.H317 May cause an allergic skin reaction.H319 Causes serious eye irritation.



ABN: 52 189 407 505 Phone: 1300 577 719 Fax: 1300 366 353 Email: glabe@sealing services.com.au Web: www.global-services.com.au 17 Ryelane Street Maddington WA AUSTRALIA

## SAFETY DATA SHEET

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

### Pictogram (s)

Exclamation mark, Health hazard



### **Precautionary Statement – Prevention**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

### **Precautionary Statement – Response**

P314 Get medical advice/attention if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of water.

P362+P364 Take off contaminated clothing and wash it before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P308+P313 IF exposed or concerned: Get medical advice/attention.

### Precautionary Statement – Storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.

### Precautionary Statement – Disposal

P501 Dispose of contents/container to an approved waste disposal plant.



ABN: 52 189 407 505 Phone: 1300 577 719 Fax: 1300 366 353 Email: glabe@sealing services.com.au Web: www.global-services.com.au 17 Ryelane Street Maddington WA AUSTRALIA

## SAFETY DATA SHEET

### Section 3 - Composition and Information on Ingredients

### Ingredients

Name	CAS	Proportion
4,4'- Diphenylmethane diisocyanate	101-68-8	>60 %
Propylene polyol diphenyl methane diisocyanate prepolymer	9048-57-1	10-<30 %

### **Section 4 - First Aid Measures**

### Inhalation

If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

### Ingestion

Do not induce vomiting. Wash out mouth thoroughly with water. Seek immediate medical attention.

### Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

### Eye

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

### **First Aid Facilities**

Eyewash, safety shower and normal washroom facilities.

### Advice to Doctor

Treat symptomatically.

### **Other Information**

For advice in an emergency, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor at once.

### **Section 5 - Firefighting Measures**

### Suitable Extinguishing Media

Use carbon dioxide, dry chemical or foam.

### **Unsuitable Extinguishing Media**

Do not use water jet.

### **Hazards from Combustion Products**

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide, hydrogen cyanide and oxides of nitrogen.

### Specific hazards arising from the chemical

This product will burn if exposed to fire.

## SAFETY DATA SHEET

**Decomposition Temperature** > 200°C

### Precautions in connection with Fire

SEALING SERVICES PTY LTD

ABN: 52 189 407 505 Phone: 1300 577 719 Fax: 1300 366 353 Email: glabe@sealing services.com.au Web: www.global-services.com.au 17 Ryelane Street Maddington WA AUSTRALIA

Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.

### **Section 6 - Accidental Release Measures**

### **Emergency Procedures**

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

For small spills, < 20 litres, absorb spilled material with inert absorbent (sand, vermiculite etc.) and put into open top containers. Do not permit to contaminate waterways, sewers or drains. Absorb the Isocyanate with sawdust or other absorbent and shovel into open top containers - do not make pressure tight. Transport to well-ventilated area (outside) and

treat with neutralising solution consisting of a mixture of 90% water, 5% detergent and 5% concentrated ammonium hydroxide. Add about 10 parts of the neutralising solution per part of Isocyanate with mixing. Allow to stand for 48 to 72 hours letting any evolved carbon dioxide escape. Do not seal.

For large amounts, > 20 litres, either pump product into or collect in suitable containers and transfer into clean closed head type drums. In case of any contamination, do not make pressure tight.

Residual contamination from spills can be cleaned up with the neutralising solution - a mixture of 90% water, 5% industrial grade detergent and 5% concentrated ammonium hydroxide.

### Section 7 - Handling and Storage

### **Precautions for Safe Handling**

Avoid inhalation of vapours and mists, and skin or eye contact. Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the build up of mists or vapours in the work atmosphere. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous residues. Maintain high standards of personal hygiene by washing hands prior to eating, drinking, smoking or using toilet facilities.

### Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 (2017)- The storage and handling of flammable and combustible liquids.

## SAFETY DATA SHEET

#### **Storage Regulations**

Classified as a Class C2 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS1940 (2017).

#### **Storage Temperatures**

Store indoors at 15 to 25°C in original, unopened containers. Protect from atmospheric moisture. Replace outage with inert Dry Nitrogen Gas. Avoid product temperatures above 50°C and below 5°C. At temperatures below 5°C crystallisation may occur.

#### **Other Information**

Store away from oxidising agents, acids, alkali, amines, direct sunlight or any source of ignition or heat.

### **Section 8 - Exposure Controls and Personal Protection**

#### **Occupational exposure limit values**

No exposure standards have been established for this material. However, the available exposure limits for ingredients are listed below:

Isocyanate TWA: 0.02 mg/m<sup>3</sup> STEL: 0.07 mg/m<sup>3</sup> Notices: Sen

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

'Sen' Notice: The substance may cause sensitization by skin contact or by inhalation.

#### **Biological Monitoring**

No biological limits allocated.

Control Banding Not available

### **Engineering Controls**

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

#### **Respiratory Protection**

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.

Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

### Eye and Face Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to



### SAFETY DATA SHEET GLOBAL FLEXITHANE 303 PART A

Infosafe No.: LQ2H2

## SAFETY DATA SHEET

relevant regulations.

Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 (series) - Eye Protectors for Industrial Applications.

### **Hand Protection**

Wear gloves of impervious material, such as PVC. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

### **Thermal Hazards**

No further relevant information available.

### **Body Protection**

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

### **Section 9 - Physical and Chemical Properties**

Properties	Description	Properties	Description
Form	Liquid	Appearance	Viscous amber liquid
Colour	Amber	Odour	Mild musty odour
Melting Point	< 0°C	Boiling Point	> 200°C (1 atm)
Decomposition Temperature	> 200°C	Solubility in Water	Insoluble, reacts slowly with water.
Solubility in Organic Solvents	Slightly soluble	рН	Not available
Vapour Pressure	< 0.01 Pascals (25°C)	Relative Vapour Density (Air=1)	> 1
Evaporation Rate	Not available	Odour Threshold	Not available
Viscosity	Not available	Volatile Component	Not available
Partition Coefficient: n- octanol/water (log value)	Not available	Density	1.01 g/mL (25°C)
Flash Point	> 150°C (DIN 51758)	Flammability	Non-flammable
Auto-Ignition Temperature	Not available	Flammable Limits - Lower	Not available
Flammable Limits - Upper	Not available	Explosion Properties	Not available
Oxidising Properties	Not available	Particle Characteristics	Not available

### Section 10 - Stability and Reactivity

#### **Reactivity** Reacts with incompatible materials.

Page 6 / 11



## SAFETY DATA SHEET

### **Chemical Stability**

Stable under normal conditions of storage and handling.

### Possibility of hazardous reactions

Avoid water as it reacts to form heat and carbon dioxide. Enough heat and pressure can be produced to rupture a closed container. The reaction with water is slow at temperatures less than 49°C, but accelerated at higher temperature and in the presence of the incompatible materials. Some reactions are violent.

### **Conditions to Avoid**

Heat, open flames, humidity, water and other sources of ignition. Avoid product temperatures above 50°C and below 5°C. At temperatures below 5°C crystallisation may occur.

### **Incompatible Materials**

Water, acids, alkalis, alcohols, and metal compounds.

### **Hazardous Decomposition Products**

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide, hydrogen cyanide and oxides of nitrogen.

### **Hazardous Polymerization**

Not available

### Section 11 - Toxicological Information

### **Toxicology Information**

Acute toxicity data for product is given below:

Acute Toxicity - Oral LD50(rat): > 10000 mg/kg

## Acute Toxicity - Dermal

LD50(rabbit): > 5000 mg/kg

### Acute Toxicity - Inhalation

#### LC50(rat): 490 aerosol/m<sup>3</sup>/4h.

Concentration of the saturated vapour of 4,4'- Diphenylmethane diisocyanate: MDI (25°C) - 0.09 mg/m<sup>3</sup>).

### Ingestion

Ingestion of this product may irritate the gastric tract causing nausea and vomiting.

### Inhalation

Harmful if inhaled. May cause respiratory irritation. Inhalation of product vapours can cause irritation of the nose, throat and respiratory system. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### Skin

Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis. May cause an allergic skin reaction.

### Eye

Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

### **Respiratory Sensitisation**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

### Skin Sensitisation

May cause an allergic skin reaction.



## SAFETY DATA SHEET

**Germ Cell Mutagenicity** Not considered to be a mutagenic hazard.

**Carcinogenicity** Suspected of causing cancer. Classified as a suspected human carcinogen.

**Reproductive Toxicity** Not considered to be toxic to reproduction.

**STOT - Single Exposure** May cause respiratory irritation.

**STOT - Repeated Exposure** May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard Not expected to be an aspiration hazard.

## Section 12 - Ecological Information

### Ecotoxicity

The available ecological data is given below.

### Persistence and degradability

Biodegradability: 0%, 28 days. Immiscible in water. Reaction with water at interface produces Carbon Dioxide and forms an insoluble and high melting point solid - polyurea.

VICES P

Degradation is expected in the atmospheric environment.

### Mobility

Movement in the environment is expected to be limited by the formation of insoluble polymers.

**Bioaccumulative Potential** Not available

Other Adverse Effects Not available

**Environmental Protection** Prevent this material entering waterways, drains and sewers.

Acute Toxicity - Fish LC0(Brachydanio rerio): > 100 mg/L/96h

Acute Toxicity - Daphnia EC50(Daphnia pulex): > 750 mg/L/24h

### Hazardous to the Ozone Layer

This product is not expected to deplete the ozone layer.

## Section 13 - Disposal Considerations

### **Disposal Considerations**

The disposal of the spilled or waste material must be done in accordance with applicable local and national regulations. To minimise personal exposure, refer to Section 8 - Exposure Controls and Personal Protection.

## Section 14 - Transport Information



## SAFETY DATA SHEET

### **Transport Information**

Road and Rail Transport (ADG Code):

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code) (7th edition).

Marine Transport (IMO/IMDG): Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Air Transport (ICAO/IATA): Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

ADG U.N. Number None Allocated

ADG Proper Shipping Name None Allocated

ADG Transport Hazard Class None Allocated

Special Precautions for User Not available

IMDG Marine pollutant No

Transport in Bulk Not available

### Section 15 - Regulatory Information

### **Regulatory Information**

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Poisons Schedule S6 Montreal Protocol Not listed Stockholm Convention Not listed

Rotterdam Convention Not listed

International Convention for the Prevention of Pollution from Ships (MARPOL) Not available





ABN: 52 189 407 505 Phone: 1300 577 719 Fax: 1300 366 353 Email: glabe@sealing services.com.au Web: www.global-services.com.au 17 Ryelane Street Maddington WA AUSTRALIA

## SAFETY DATA SHEET

Agricultural and Veterinary Chemicals Act 1994 Not listed

Basel Convention Not listed

### Section 16 - Any Other Relevant Information

### **Date of Preparation**

SDS Reviewed: December 2022 Supersedes: March 2018 and July 2013

Version Number 3.0

### Literature References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

Standard for the Uniform Scheduling of Medicines and Poisons.

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Code of Practice for Supply Diversion into Illicit Drug Manufacture.

National Code of Practice for Chemicals of Security Concern.

Agricultural Compounds and Veterinary Chemicals Act.

International Agency for Research on Cancer (IARC) Monographs.

Montreal Protocol on Substances that Deplete the Ozone Layer.

Stockholm Convention on Persistent Organic Pollutants (POPs).

Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade.

Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and Their Disposal.

International Air Transport Association (IATA) Dangerous Goods Regulations.

International Maritime Dangerous Goods (IMDG) Code.

Workplace exposure standards for airborne contaminants.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

Globally Harmonised System of Classification and Labelling of Chemicals (7th revised edition).

Code of Practice: Managing Noise and Preventing Hearing Loss at Work.

### **User Codes**

User Title Label	User Codes
Task #	25578
Task #	4899

## **END OF SDS**

#### © Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.

## SAFETY DATA SHEET

