



PRODUCT DATA SHEET

PERMALUX SUPACOAT - INTERIOR LO SHEEN

PERMALUX SUPACOAT - INTERIOR LO SHEEN is a single pack, non hazardous, non toxic water based paint system that offers exceptional coverage and performance over a variety of suitably sealed substrates of Concrete, Gyprock, Masonry and Fibre Cement.

Physical Characteristics

Product type	Solvent-free dispersion of modified acrylic resins with mineral fillers and lightfast pigments
Appearance	Lo Sheen Viscous white liquid can be tinted
Viscosity@25°C	4000 mPa
Density @ 25°C	1.40 Kg/Lt
Solids	Approximately 40%
Application Rate	Approximately 12-14m ² /LT @ 25micron DFT
Film Formation	Temperatures above 10°C
Susceptibility to Frost	Avoid freezing conditions. Store above +2°C
Storage Stability	2 Years or more in suitable conditions (18°C to 50 °C)
Cleaning Agent	Water
Danger Classification	Not Applicable. Non Hazardous.

Technical Features

- Water based
- Easy Application
- Superior Coverage
- Low Splatter
- Low Odour

Application Information

Surface Preparation	Surfaces must be clean, stable and free of oil and grease. Loose particles should be removed and repairs carried out if required.
---------------------	---

Application Information - continued

Application Conditions Do not apply if the ambient temperature is below 10°C or if the temperature of the surface may fall below 10°C during the drying period.

Do not apply when ambient and substrate temperatures are above 38°C. Do not apply if the relative humidity is above 85% or if dew point is likely to be reached during the drying period.

Avoid exposure to steam and condensation for 48hrs after painting. High humidity and low temperatures will affect cure time.

Application Process Stir well with a broad flat stirrer. Apply by brush or paint roller and via airless spray equipment at 5 bar pressure and a minimum 0.21mm to 0.30mm nozzle size.

Drying Time Touch dry 30 minutes. Recoat 2hrs

Equipment Cleanup:

Wash all equipment thoroughly with water.

Safety Precautions:

Avoid ingestion and contact with skin or eyes. Wear protective goggles and waterproof gloves.

Pack Sizes:

4litres, 10litres, 15litres, 200 litres, 1000 litres

Contact Point

For further information and technical assistance please contact:

Uniseal Manufacturing
17 Ryelane Street
Maddington WA 6109
Tel: 1300 577 719
Fax: 1300 366 353
Email: uniseal@sealingservices.com.au
www.unisealcoatings.com.au



Uniseal Manufacturing is a division of the Global Group of Companies

DISCLAIMER: Please note that this information is supplied based on field and laboratory tests and is, to the best of our knowledge, deemed to be correct, however, no guarantee of the accuracy of this information in all instances is intended or implied and Uniseal Manufacturing accepts no liability for any failure or loss that may result from the application process. Please contact Uniseal Manufacturing if additional or task-specific information is required.