

# PRODUCT DATA SHEET

## PREMIUM GRASS MARKING PAINT

PREMIUM GRASS MARKING PAINT is a water based flat pva paint made specifically for marking on all grass surfaces where a distinct but temporary mark is required. Premium Grass Marking Paint is available in white, black or selected range of colours and will not damage or kill grass and will last for up to 1 month depending on weather and growth of grass. If a more permanent line is required a small amount of Roundup can be added to the paint to kill the grass underneath.

### Physical Characteristics

Product type	Water based dispersion of modified resins
Appearance	Viscous thixotropic liquid. White, Black or selected colour range
Density @ 25°C	1.48 Kg/Ltr
Solids	Approximately 50% by weight.
Application Rate	8-10m <sup>2</sup> /LT
Susceptibility to Frost	Avoid freezing conditions. Store above +2°C
Storage Stability	2 Years or more in suitable conditions (18°C to 50 °C)
Cleaning Agent	Water
Danger Classification	Not Applicable. Non Hazardous.

### Technical Features

- Water based
- Brilliant White and Black
- Distinct line that stands out
- Fast drying for quick turn around
- Water based, non toxic - before, during and after use.

### Application Information

Surface Preparation	Surfaces must be clean, stable and free of oil and grease. Loose particles should be removed and repairs carried out if require
---------------------	---

## Application Information - continued

Application Conditions	Do not apply if the ambient temperature is below 10°C or during rain or if the temperature of the surface may fall below 10°C during the drying period. Do not apply when ambient and substrate temperatures are above 38°C. Do not apply if the relative humidity is above 85% or if dew point is likely to be reached during the drying period.
Application Process	Can be applied by brush roller and with convention spray equipment.
Application Rates	8-10m <sup>2</sup> /LT. Application rate may vary depending on porosity and nature of the surface. May be diluted with 2 to 4 parts of water depending on surface and equipment.

## Equipment Cleanup

Wash all equipment thoroughly with water.

## Safety Precautions:

Avoid ingestion and contact with skin or eyes. Wear protective goggles and waterproof gloves.

## Pack Sizes:

20 litres, 200 litres, 1000 litres

## Contact Point

For further information and technical assistance please contact:

Uniseal Manufacturing  
17 Ryelane Street  
Maddington WA 6109  
Tel: 1300 577 719  
Fax: 1300 366 353  
Email: [uniseal@sealingservices.com.au](mailto:uniseal@sealingservices.com.au)  
[www.unisealcoatings.com.au](http://www.unisealcoatings.com.au)



Uniseal Manufacturing is a division  
of the Global Group of Companies

DISCLAIMER: Please note that this information is supplied based on field and laboratory tests and is, to the best of our knowledge, deemed to be correct, however, no guarantee of the accuracy of this information in all instances is intended or implied and Uniseal Manufacturing accepts no liability for any failure or loss that may result from the application process. Please contact Uniseal Manufacturing if additional or task-specific information is required.